


Series 3

# MR16OUT


Serial I/O

16-output Interface Panel



## Features

- 16 programmable relay outputs; 2 dedicated inputs
- AES 128/256 Data Encryption
- UL 294 recognized, CE compliant, FCC, RoHS
- Easily integrates lighting, heating/cooling, door or elevator control systems
- Initiates commands by operator, by time schedules, or by events
- Built-in capacity to control and respond to external device commands
- Allows the clustering of up to 16 uniquely monitored devices easily and compactly
- RS-485 host connectivity



- **Open Architecture:** High performance, reliable platform
- **Easy Expansion:** Adds functionality and flexibility to existing access control systems
- **Enhanced Security:** Embedded crypto memory chip provides secured layer of encryption to protect sensitive data
- **Versatile Interoperability:** Same reliable interface and identical footprint as Series 2 Mercury IO modules, enabling seamless upgrades for existing deployments

**The IMRON MR-Series 3 Serial Input/ Output (SIO) modules** enable system expansion of the IMRON Intelligent Controllers as part of the distributed architecture. The enhanced modules offer an improved processor and increased memory, plus features an embedded crypto memory chip that provides a secured layer of encryption to onboard sensitive data. Built on the Authentic Mercury open platform, Series 3 modules provide the necessary flexibility and hardware configuration.

The MR16OUT-S3 is dedicated to point control and monitoring, providing 16 general-purpose outputs as Form C relay contacts. The MR16OUT-S3 also provides individually configurable parameters that can be set for timing and for fail-safe versus fail-secure modes. The MR16OUT-S3 is configurable to control a variety of outboard devices for general facility control such as lighting, heating/cooling, door and elevator control. Devices can also be activated by the condition of selected system devices, either locally or regionally, without host intervention.


The MR16OUT Series 3 is the latest generation door interface module providing an open architecture solution.

# MR16OUT

## Application Notes

The IMRON MR16OUT-S3 is an essential component to support the flexible, building block approach to access control system design. The versatile MR16OUT-S3 offers unmatched power to broaden the range of devices and building controls (such as lighting or HVAC) that can be included in system design. Relay operation can be initiated by direct operator commands, by time schedules, or by event-based procedures. The relays support “On,” “Off,” “Pulse” and “Repeating Pulse” commands. A pulse can range from .1 seconds to over 18 hours.

Specifications	
<b>Primary Power</b>	12-24 Vdc +/- 10%, 1100mA maximum
<b>Host Communication</b>	RS-485, 2-wire, 4,000' (twisted pair with shield, Belden 9841)
<b>Inputs</b>	2 Dedicated: Tamper and Power Monitor
<b>Output Relays</b>	Sixteen Form-C Relays: Normally open contact (NO): 5A @ 30 Vdc resistive Normally closed contact (NC): 3A @ 30 Vdc resistive
<b>Dimensions</b>	6.0" W x 8.0" L x 1.0" H (152mm W x 203mm L x 25mm H)
<b>Temperature</b>	0-70 °C operational, -55-85 °C storage
<b>Humidity</b>	5 to 95% RHNC
<b>Standards</b>	UL 294 recognized, CE compliant, RoHS, FCC Part 15 Subpart B



The Authentic Mercury open platform delivers quality assurance derived from the most proven and reliable hardware in the industry. Driven by our engineering excellence and technology leadership, Authentic Mercury hardware is designed as an access control platform that easily encompasses emerging technologies, changing industry standards and evolving system environments. Make yours Authentic, **Make sure its Merc.**